

**Cambridge  
International  
AS & A Level**

**Cambridge International Examinations**  
Cambridge International Advanced Subsidiary and Advanced Level

CANDIDATE  
NAME

|  |
|--|
|  |
|--|

CENTRE  
NUMBER

|  |  |  |  |  |
|--|--|--|--|--|
|  |  |  |  |  |
|--|--|--|--|--|

CANDIDATE  
NUMBER

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|



**COMPUTER SCIENCE**

**9608/42**

Paper 4 Further Problem-solving and Programming Skills

**October/November 2018**

**2 hours**

Candidates answer on the Question Paper.

No Additional Materials are required.

No calculators allowed.

**READ THESE INSTRUCTIONS FIRST**

Write your Centre number, candidate number and name in the spaces at the top of this page.

Write in dark blue or black pen.

You may use an HB pencil for any diagrams, graphs or rough working.

Do not use staples, paper clips, glue or correction fluid.

**DO NOT WRITE IN ANY BARCODES.**

Answer **all** questions.

No marks will be awarded for using brand names of software packages or hardware.

At the end of the examination, fasten all your work securely together.

The number of marks is given in brackets [ ] at the end of each question or part question.

The maximum number of marks is 75.

This document consists of **15** printed pages and **1** blank page.



**2****1** A bank provides bank accounts to customers.

The following pseudocode represents the operation of the bank account.

```
CALL OpenAccount()
CALL AccountLifeTime()
CALL CloseAccount()

PROCEDURE AccountLifeTime()
    REPEAT
        CALL Transactions()
    UNTIL AccountClosed() = TRUE
ENDPROCEDURE

PROCEDURE CloseAccount()
    IF ReopenAccount() = TRUE
    THEN
        CALL FlagToReopen()
    ELSE
        CALL DeletePermanently()
    ENDIF
ENDPROCEDURE
```

**(a)** Complete the JSP structure diagram for this bank account from the pseudocode given.

Bank account

[6]

**3**

**(b)** A transaction can be a credit (deposit) or a debit (withdrawal).


There are two types of transaction that are credits (deposits). These are:

- SWIFT payment
- BACS payment

There are three types of transaction that are debits (withdrawals). These are:

- Debit card payment
- Cheque payment
- Online payment

Complete the JSP structure diagram to represent these additional requirements.



[4]

2 A declarative language is used to represent facts and rules about dogs that perform tasks to help people.

```
01 type(pointer, gundog).
02 type(flushing, gundog).
03 type(retriever, gundog).
04
05 is_a(labrador, retriever).
06 is_a(newfoundland, retriever).
07 is_a(cocker_spaniel, flushing).
08 is_a(springer_spaniel, flushing).
09 is_a(king_charles, flushing).
10 is_a(english_setter, pointer).
11 is_a(irish_setter, pointer).
12
13 fav_bird(pointer, grouse).
14 fav_bird(flushing, pheasant).
15 fav_bird(retriever, waterfowl).
16
17 type(X, Y) IF is_a(Z, X) AND type(Z, Y).
```

These clauses have the following meaning:

| Clause | Explanation                                                    |
|--------|----------------------------------------------------------------|
| 01     | A pointer is a type of gundog.                                 |
| 05     | A labrador is an example of a retriever.                       |
| 13     | The favourite bird of a pointer is a grouse.                   |
| 17     | X is a type of Y if Z is an example of X and Z is a type of Y. |

(a) More facts are to be included.

A **standard poodle** is an example of a waterdog. A waterdog is a type of gundog.

Write the additional clauses to record these facts.

```
18 .....
19 .....
```

[2]

5

(b) Using the variable `P`, the goal`is_a(P, retriever)`

returns

`P = labrador, newfoundland`

Write the result returned by the goal

`is_a(H, pointer)``H = .....` [2](c) Write a query, using the variable `W`, to find out what an **irish setter** is an example of.`.....` [2](d) `Y` is the favourite bird of dog `X`.

Complete the following rule:

`fav_bird(X, Y) IF .....``.....` [3]

(e) State the value returned by the goal

`NOT(is_a(labrador, retriever))``.....` [1]

6

- 3 A bubble sort algorithm is used to sort an integer array, `List`. This algorithm can process arrays of different lengths.

(a) Write **pseudocode** to complete the bubble sort algorithm shown.

```

01 FOR Outer ← ..... TO 0 STEP - 1
02   FOR Inner ← 0 TO (.....)
03     IF ..... > .....
04       THEN
05         Temp ← .....
06         List[Inner] ← .....
07         List[Inner + 1] ← .....
08       ENDIF
09   ENDFOR
10 ENDFOR

```

[7]

(b) (i) State the order of the sorted array.

..... [1]

(ii) State which line of the algorithm you would change to sort the array into the opposite order.

State the change you would make.

Line .....

Change .....

..... [1]

[4]

4 A circus is made up of performers. There are three types of performer: clown, acrobat and aerial.

The following data are stored for each performer.

- First name
- Last name
- Secondary role (that can be edited)
- Stage name (that can be edited)
- Type of performer (PerfType)

The following statements apply to performers.

- An acrobat may or may not use fire in his or her act.
- An aerial performer can be one of two types: either catcher or flyer.
- Each clown has an item, such as a water-spraying flower or a unicycle.
- Each clown also has a musical instrument, such as a guitar or an oboe.

Each of the three types of performer has a method that will display all of the information about that performer in a specific format. For example:

*Sally Superstar (real name Sally Smith) is an acrobat. Fire is part of Sally Superstar's act. When not performing, Sally Superstar is a set changer.*

(a) Complete the following class diagram to show the **attributes**, **methods** and **inheritance** for the program.

You do not need to write the get and set methods.

| Performer                                                                                                    |
|--------------------------------------------------------------------------------------------------------------|
| FirstName : STRING<br>LastName : STRING<br>SecondaryRole : STRING<br>StageName : STRING<br>PerfType : STRING |
| Constructor()<br>EditSecondaryRole()<br>EditStageName()                                                      |

| Acrobat                          |
|----------------------------------|
| UseFire : BOOLEAN                |
| Constructor()<br>PerformerInfo() |

| Clown                  |
|------------------------|
| .....<br>.....         |
| Constructor()<br>..... |

| Aerial                 |
|------------------------|
| .....                  |
| Constructor()<br>..... |

[4]

Program code

[5]

10

**(c)** The program will display the acrobat information as follows:

*Sally Superstar (real name Sally Smith) is an acrobat. Fire is part of Sally Superstar's act. When not performing, Sally Superstar is a set changer.*

Write **program code** for the Acrobat class.

Programming language .....

Program code

This image shows a full page of white paper with horizontal dashed lines, typical of primary school handwriting practice paper. The lines are evenly spaced and run across the entire width of the page. There are no margins, text, or other markings on the paper.

.....

.....

.....

.....

.....

..... [8]

(d) Information about a performer is as follows:

*Amazing Alex (real name Alex Tan) is an acrobat. Fire is part of Alex's act. When not performing, Amazing Alex is a popcorn seller.*

(i) Write **program code** to create an instance of an object with the identifier `Acrobat_1`.

All attributes of the instance should be fully initialised.

.....

.....

.....

..... [3]

(ii) Explain **inheritance** with reference to the circus example.

.....

.....


.....

.....

.....

.....

..... [2]



[5]

**13**

- (b)** There are three teams working on the project. Each team is able to work on any of the activities.

Explain, with reference to the PERT chart, how work can be allocated to the three teams.

.....

.....

.....

.....

.....

..... [2]

- (c)** The PERT chart is used to calculate the critical path for the project.

- (i)** List the activities that form the critical path using the given PERT chart on page 12.

..... [1]

- (ii)** Explain the importance of the critical path for project delivery.

.....

.....

.....

.....

..... [2]

6 A linked list abstract data type (ADT) is created. This is implemented as an array of records. The records are of type `ListElement`.

An example of a record of `ListElement` is shown in the following table.

| Data Item | Value      |
|-----------|------------|
| Country   | "Scotland" |
| Pointer   | 1          |

(a) (i) Use **pseudocode** to write a definition for the record type, `ListElement`.

.....

.....

.....

.....

..... [3]

(ii) Use **pseudocode** to write an array declaration to reserve space for only 15 nodes of type `ListElement` in an array, `CountryList`. The lower bound element is 1.

..... [2]

(b) The program stores the position of the last node in the linked list in `LastNode`. The last node always has a `Pointer` value of `-1`. The position of the node at the head of the list is stored in `ListHead`.

After some processing, the array and variables are in the following state.

| ListHead |
|----------|
| 1        |
| LastNode |
| 3        |

| CountryList |            |         |
|-------------|------------|---------|
|             | Country    | Pointer |
| 1           | "Wales"    | 2       |
| 2           | "Scotland" | 4       |
| 3           |            | -1      |
| 4           | "England"  | 5       |
| 5           | "Brazil"   | 6       |
| 6           | "Canada"   | 7       |
| 7           | "Mexico"   | 8       |
| 8           | "Peru"     | 9       |
| 9           | "China"    | 10      |
| 10          |            | 11      |
| 11          |            | 12      |
| 12          |            | 13      |
| 13          |            | 14      |
| 14          |            | 15      |
| 15          |            | 3       |

## 15

A **recursive** algorithm searches the list for a value, deletes that value, and updates the required pointers. When a node value is deleted, it is set to empty "" and the node is added to the end of the list.

A node value is deleted using the pseudocode statement

```
CALL DeleteNode("England", 1, 0)
```

Complete the following **pseudocode** to implement the DeleteNode procedure.

```
PROCEDURE DeleteNode(NodeValue: STRING, ThisPointer : INTEGER,
                    PreviousPointer : INTEGER)

IF CountryList[ThisPointer].Value = NodeValue
THEN
    CountryList[ThisPointer].Value ← ""
    IF ListHead = .....
    THEN
        ListHead ← .....
    ELSE
        CountryList[PreviousPointer].Pointer ← CountryList[ThisPointer].Pointer
    ENDIF
    CountryList[LastNode].Pointer ← .....
    LastNode ← ThisPointer
    .....
ELSE
    IF CountryList[ThisPointer].Pointer <> -1
    THEN
        CALL DeleteNode(NodeValue, .....,
                        ThisPointer)
    ELSE
        OUTPUT "DOES NOT EXIST"
    ENDIF
ENDIF
ENDIF
ENDPROCEDURE
```

[5]

**BLANK PAGE**

---

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge International Examinations Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at [www.cie.org.uk](http://www.cie.org.uk) after the live examination series.

Cambridge International Examinations is part of the Cambridge Assessment Group. Cambridge Assessment is the brand name of University of Cambridge Local Examinations Syndicate (UCLES), which is itself a department of the University of Cambridge.