GradeMax

Cambridge International AS & A Level

Cambridge Assessment International Education
Cambridge International Advanced Subsidiary and Advanced Level

CANDIDATE NAME

CENTRE NUMBER

CANDIDATE NUMBER

1209867308

COMPUTER SCIENCE **9608/22**

Paper 2 Fundamental Problem-solving and Programming Skills **October/November 2019**

2 hours

Candidates answer on the Question Paper.

No Additional Materials are required.

No calculators allowed.

READ THESE INSTRUCTIONS FIRST

Write your centre number, candidate number and name in the spaces at the top of this page.
Write in dark blue or black pen.
You may use an HB pencil for any diagrams, graphs or rough working.
Do not use staples, paper clips, glue or correction fluid.
DO **NOT** WRITE IN ANY BARCODES.

Answer **all** questions.
No marks will be awarded for using brand names of software packages or hardware.

At the end of the examination, fasten all your work securely together.
The number of marks is given in brackets [ ] at the end of each question or part question.

The maximum number of marks is 75.

This document consists of **18** printed pages and **2** blank pages.

DC (ST) 171121/3
© UCLES 2019

Cambridge Assessment International Education

[Turn over

PapaCambridge

GradeMax

1 Study the following pseudocode.

```
PROCEDURE FillTank()

   DECLARE Tries : INTEGER
   DECLARE Full : BOOLEAN

   Tries ← 1

   Full ← ReadSensor("F1")

   IF NOT Full
      THEN
         WHILE NOT Full AND Tries < 4
            CALL TopUp()
            Full ← ReadSensor("F1")
            Tries ← Tries + 1
         ENDWHILE
         IF Tries > 3
            THEN
               OUTPUT "Too many attempts"
            ELSE
               OUTPUT "Tank now full"
         ENDIF
      ELSE
         OUTPUT "Already full"
   ENDIF

ENDPROCEDURE
```

(a) (i) The pseudocode includes features that make it easier to read and understand.

State **three** such features.

Feature 1 .....

Feature 2 .....

Feature 3 .....

[3]

© UCLES 2019

PapaCambridge

GradeMax

(ii) Draw a program flowchart to represent the algorithm implemented in the pseudocode. Variable declarations are not required in program flowcharts.

[5]

PapaCambridge

(b) (i) Programming languages support different data types.

Complete the table by giving a suitable data type for each example value.

Example value	Data type
`43`	
`TRUE`	
`-273.16`	
`"-273.16"`	

[4]

(ii) Evaluate each expression in the following table.

If an expression is invalid then write 'ERROR'.

Refer to the **Appendix** on page 18 for the list of built-in functions and operators.

Expression	Evaluates to
`RIGHT("Stop", 3) & LEFT("ich", 2)`	
`MID(NUM_TO_STRING(2019), 3, 1)`	
`INT(NUM_TO_STRING(-273.16))`	
`INT(13/2)`	

[4]

© UCLES 2019

PapaCambridge

GradeMax

2 **(a)** Describe the program development cycle with reference to the following:

- source code
- object code
- corrective maintenance.

.....

.....

.....

.....

.....

.....

.....

.....

..... [3]

(b) Give **three** features of an Integrated Development Environment (IDE) that can help with **initial error detection** while writing the program.

1 .....

.....

2 .....

.....

3 .....

.....

[3]

© UCLES 2019

[Turn over

PapaCambridge

3 A student is developing a program to search through a string of numeric digits to count how many times each digit occurs. The variable `InString` will store the string and the 1D array `Result` will store the count values.

The program will:

- check each character in the string to count how many times each digit occurs
- record the count for each digit using the array
- output the count for each element of the array together with the corresponding digit.

(a) The array `Result` is a 1D array of type `INTEGER`.

Write **pseudocode** to declare the array and to initialise all elements to zero.

.....

.....

.....

.....

.....

..... [3]

PapaCambridge

GradeMax

(b) Write the **pseudocode** for the program.

Declare any variables you use. Do not implement the code as a subroutine.

Refer to the **Appendix** on page 18 for the list of built-in functions and operators.

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [8]

PapaCambridge

GradeMax

4 A program is being written to control the operation of a portable music player. One part of the program controls the output volume.

The player has two buttons, one to increase the volume and one to decrease it. Whenever a button is pressed, a procedure `Button()` is called with a parameter value representing the button as follows:

Button	Parameter value
Volume increase	10
Volume decrease	20

For example, pressing the volume increase button three times followed by pressing the volume decrease button once would result in the calls:

```
CALL Button(10) // VolLevel increased by 1
CALL Button(10) // VolLevel increased by 1
CALL Button(10) // VolLevel increased by 1
CALL Button(20) // VolLevel decreased by 1
```

The program makes use of two global variables of type `INTEGER` as follows:

Variable	Description
`VolLevel`	The current volume setting. This must be in the range 0 to 49.
`MaxVol`	A value that can be set to limit the maximum value of `VolLevel`, in order to protect the user's hearing. A value in the range 1 to 49 indicates the volume limit. A value of zero indicates that no volume limit has been set.

The procedure `Button()` will modify the value of `VolLevel` depending on which button has been pressed and whether a maximum value has been set.

© UCLES 2019

PapaCambridge

GradeMax

(a) Write **pseudocode** for the procedure `Button()`. Declare any additional variables you use.

The value of `MaxVol` should **not** be changed within the procedure.

Parameter validation is **not** necessary.

.....

.....

.....

(b) The procedure `Button()` is to be tested using black-box testing.

Fill in the gaps below to define **three** tests that could be carried out.

TEST 1 – `VolLevel` is changed

Parameter value: 10

`MaxVol`: .....

`VolLevel` value before call to `Button()`: 48

`VolLevel` expected value after call to `Button()`: .....

TEST 2 – `VolLevel` is **not** changed

Parameter value: 10

`MaxVol`: 34

`VolLevel` value before call to `Button()`: .....

`VolLevel` expected value after call to `Button()`: .....

TEST 3 – `VolLevel` is **not** changed

Parameter value: .....

`MaxVol`: 40

`VolLevel` value before call to `Button()`: 0

`VolLevel` expected value after call to `Button()`: .....

[6]

© UCLES 2019

PapaCambridge

GradeMax

(c) The testing stage is part of the program development cycle.

(i) The program for the music player has been completed. The program does not contain any syntax errors, but testing could reveal further errors.

Identify **and** describe **one different** type of error that testing could reveal.

Type .....

Description .....

.....

.....
[2]

(ii) Stub testing is a technique often used in the development of modular programs.

Describe the technique.

.....

.....

.....

.....

.....

..... [3]

© UCLES 2019

[Turn over

PapaCambridge

GradeMax

5 The module headers for three modules in a program are defined in pseudocode as follows:

Pseudocode module header
`PROCEDURE Lookup(P4 : INTEGER, BYREF M4 : STRING)`
`FUNCTION Update(T4 : INTEGER) RETURNS INTEGER`
`FUNCTION Validate(S2 : INTEGER, P3 : STRING) RETURNS BOOLEAN`

A fourth module, `Renew()`, calls the three modules in the following sequence.

```
Validate()
Lookup()
Update()
```

Draw a structure chart to show the relationship between the four modules and the parameters passed between them.

[7]

© UCLES 2019

PapaCambridge

GradeMax

Question 6 begins on the next page.

PapaCambridge

GradeMax

6 A text file, `StudentList.txt`, contains a list of information about students in a school.

Each line of the file contains a reference, name and date of birth for one student. All the information is held as strings and separated by the asterisk character (`'*'`) as follows:

```
<Reference>'*'<Name>'*'<Date Of Birth>
```

An example of one line from the file is:

```
"G1234*Aleza Hilton*05062001"
```

The reference string may be five or eight characters in length and is unique for each student. It is made up of alphabetic and numeric characters only.

A global 1D array, `Leavers`, contains the references of all students who have recently left the school. The array consists of 500 elements of data type `STRING`. Unused elements contain the empty string `""`.

A program is to be written to produce a new text file, `UpdatedList.txt`, containing information only for students who are still attending the school.

The program is to be implemented as several modules. The outline description of three of these is as follows:

Module	Outline description

`ProcessStudentList()`	• Read each line from the file `StudentList.txt`
	  ◦ Check whether the `Reference` appears in the array using `SearchLeavers()`
	  ◦ If the `Reference` does **not** appear then write the line to the file `UpdatedList.txt`
	• Return the number of lines **not** copied.

`SearchLeavers()`	• Search for a given `Reference` in the array `Leavers` • If the `Reference` is found, return `TRUE`, otherwise return `FALSE`
`CountTimes()`	• Take two parameters: the name of an array and a string. • Count the number of elements that are the same as the string. Return the count value.

© UCLES 2019

PapaCambridge

GradeMax

(a) Write **program code** for the module `SearchLeavers()`. Declare any additional variables you use.

Visual Basic and Pascal: You should include the declaration statements for variables.
Python: You should show a comment statement for each variable used with its data type.

Programming language .....

Program code

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [6]

© UCLES 2019

[Turn over

PapaCambridge

GradeMax

(b) Write **pseudocode** for the module `ProcessStudentList()`.

The module description is repeated here for reference.

Module	Outline description

`ProcessStudentList()`	• Read each line from the file `StudentList.txt`
	  ◦ Check whether the `Reference` appears in the array using `SearchLeavers()`
	  ◦ If the `Reference` does **not** appear then write the line to the file `UpdatedList.txt`
	• Return the number of lines **not** copied.

PapaCambridge

GradeMax

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [9]

(c) `CountTimes()` is to be used to count how many unused elements there are in the `Leavers` array. An unused element is one that contains an empty string.

The module description is repeated here for reference.

Module	Outline description
`CountTimes()`	• Take two parameters: the name of an array and a string. • Count the number of elements that are the same as the string. Return the count value.

Write a statement in **program code** that uses `CountTimes()` to assign the count of unused elements to the variable `Result`.

Programming language .....

Program code

.....

..... [3]

© UCLES 2019

PapaCambridge

GradeMax

Appendix

Built-in functions (pseudocode)

Each function returns an error if the function call is not properly formed.

`MID(ThisString : STRING, x : INTEGER, y : INTEGER) RETURNS STRING`
returns a string of length `y` starting at position `x` from `ThisString`

Example: `MID("ABCDEFGH", 2, 3)` returns `"BCD"`

`LENGTH(ThisString : STRING) RETURNS INTEGER`
returns the integer value representing the length of `ThisString`

Example: `LENGTH("Happy Days")` returns `10`

`LEFT(ThisString : STRING, x : INTEGER) RETURNS STRING`
returns leftmost `x` characters from `ThisString`

Example: `LEFT("ABCDEFGH", 3)` returns `"ABC"`

`RIGHT(ThisString: STRING, x : INTEGER) RETURNS STRING`
returns rightmost `x` characters from `ThisString`

Example: `RIGHT("ABCDEFGH", 3)` returns `"FGH"`

`INT(x : REAL) RETURNS INTEGER`
returns the integer part of `x`

Example: `INT(27.5415)` returns `27`

`NUM_TO_STRING(x : REAL) RETURNS STRING`
returns a string representation of a numeric value.
Note: This function will also work if `x` is of type `INTEGER`

Example: `NUM_TO_STRING(87.5)` returns `"87.5"`

`STRING_TO_NUM(x : STRING) RETURNS REAL`
returns a numeric representation of a string.
Note: This function will also work if `x` is of type `CHAR`

Example: `STRING_TO_NUM("23.45")` returns `23.45`

Operators (pseudocode)

Operator	Description
`&`	Concatenates (joins) two strings Example: `"Summer" & " " & "Pudding"` produces `"Summer Pudding"`
`AND`	Performs a logical `AND` on two Boolean values Example: `TRUE AND FALSE` produces `FALSE`
`OR`	Performs a logical `OR` on two Boolean values Example: `TRUE OR FALSE` produces `TRUE`

© UCLES 2019

PapaCambridge

GradeMax

BLANK PAGE

© UCLES 2019

PapaCambridge

GradeMax

BLANK PAGE

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge Assessment International Education Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cambridgeinternational.org after the live examination series.

Cambridge Assessment International Education is part of the Cambridge Assessment Group. Cambridge Assessment is the brand name of the University of Cambridge Local Examinations Syndicate (UCLES), which itself is a department of the University of Cambridge.

© UCLES 2019

PapaCambridge