



Mark Scheme (Results)

October 2024

Pearson Edexcel International Advanced
Subsidiary Level In Physics (WPH12) Paper 01
Waves and Electricity

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk. Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

October 2024

Question Paper Log Number: P78395A

Publications Code: WPH12_01_2410_MS

All the material in this publication is copyright

© Pearson Education Ltd 2024

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Mark scheme notes

Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. **It is not a set of model answers.**

1. Mark scheme format

- 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the MS has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'
- 1.2 Bold lower case will be used for emphasis e.g. '**and**' when two pieces of information are needed for 1 mark.
- 1.3 Round brackets () indicate words that are not essential e.g. "(hence) distance is increased".
- 1.4 Square brackets [] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].

2. Unit error penalties

- 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally mean that the final calculation mark will not be awarded.
- 2.2 This does not apply in 'show that' questions or in any other question where the units to be used have been given, for example in a spreadsheet.
- 2.3 The mark will not be awarded for the same missing or incorrect unit only once within one clip in open.
- 2.4 Occasionally, it may be decided not to insist on a unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
- 2.5 The mark scheme will indicate if no unit error is to be applied by placing brackets around the unit.

3. Significant figures

- 3.1 Use of too many significant figures in the theory questions will not prevent a mark being awarded if the answer given rounds to the answer in the MS.
- 3.2 Too few significant figures will mean that the final mark cannot be awarded in 'show that' questions where one more significant figure than the value in the question is needed for the candidate to demonstrate the validity of the given answer.
- 3.3 The use of one significant figure might be inappropriate in the context of the question e.g. reading a value off a graph. If this is the case, there will be a clear indication in the MS.
- 3.4 The use of $g = 10 \text{ m s}^{-2}$ or 10 N kg^{-1} instead of 9.81 m s^{-2} or 9.81 N kg^{-1} will be penalised by one mark (but not more than once per clip). Accept 9.8 m s^{-2} or 9.8 N kg^{-1}
- 3.5 In questions assessing practical skills, a specific number of significant figures will be required e.g. determining a constant from the gradient of a graph or in uncertainty calculations. The MS will clearly identify the number of significant figures required.

4. Calculations

- 4.1 **use of** the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
- 4.2 If a 'show that' question is worth 2 marks, then both marks will be available for a reverse working. If the question is worth 3 marks then only 2 marks will be available.
- 4.3 The mark scheme will show a correctly worked answer for illustration only.

5. Quality of Written Expression

- 5.1 Questions that assess the ability to show a coherent and logically structured answer are marked with an asterisk.
- 5.2 Marks are awarded for indicative content and for how the answer is structured.
- 5.3 Linkage between ideas, and fully-sustained reasoning is expected.


Question Number	Answer	Mark
1	B is the correct answer A is not correct because intensity is power per unit area C is not correct because intensity should be power per unit area on a surface D is not correct because intensity should be power per unit area on a surface	1
2	D is the correct answer A is not correct because the electrons need to move to lower energy levels and emit photons. B is not correct because the electrons need to move to lower energy levels. C is not correct because the electrons need to emit photons.	1
3	A is the correct answer B is not correct because the distance should be doubled. C is not correct because the time should be halved. D is not correct because the time should be halved and the expression is inverted.	1
4	B is the correct answer A is not correct because the 0.7s is not the time period of the wave C is not correct because the 0.4s is not the time period of the wave D is not correct because $0.4\text{ s} - 0.1\text{ s}$ is only half the time period of the wave	1
5	D is the correct answer A is not correct because both the resistance and lattice vibrations should increase. B is not correct because the resistance should increase. C is not correct because the lattice vibrations should increase.	1
6	D is the correct answer A is not correct because the current should increase and the potential difference should increase. B is not correct because the current should increase. C is not correct because the potential difference should increase.	1
7	B is the correct answer A is not correct because the de Broglie wavelength would be 4λ. C is not correct because the de Broglie wavelength would be 0.5λ. D is not correct because the de Broglie wavelength would be 0.125λ.	1
8	C is the correct answer A is not correct because the resistance of the $7\ \Omega$ and $18\ \Omega$ resistors in parallel is not correct. B is not correct because the resistance of the $7\ \Omega$ and $18\ \Omega$ resistors in parallel is not correct and there is a short circuit around the $4\ \Omega$ resistor. D is not correct because there is a short circuit around the $4\ \Omega$ resistor.	1

9	C is the correct answer A is not correct because this would describe the motion if it was a stationary wave. B is not correct because in a complete time period F and G would then reverse direction again. D is not correct because the wave is travelling to the right, not to the left.	1
10	C is the correct answer A is not correct because this gives the current. B is not correct because this gives the potential difference across the $20\ \Omega$ resistor. D is not correct because this gives $1/\text{power}$.	1

Question Number	Answer	Mark
11	Electrons can behave as waves (1)	2
	Because the rings show diffraction / interference (1)	
Total for question 11		2

Question Number	Answer	Mark
12	The current in each wire is the same (1)	3
	The (cross-sectional) area of each wire is the same (1)	
	Because $I = nqvA$ the (average) velocity of electrons (in the copper wires) is less (than that in the nichrome wire) (1)	
	Total for question 12	3

Question Number	Answer	Mark
13(a)	Oscillations / vibrations are perpendicular to the <u>direction</u> of energy transfer of the wave (1) Or Oscillations / vibrations are perpendicular to the <u>direction</u> of wave travel / propagation	1
13(b)	The paths are different lengths / distances (1) Or There is a path difference If the path difference is a whole number of wavelengths (1) Or path difference = $n\lambda$ where n is an integer Waves are in phase (so constructive interference occurs) (1) Or there is a phase difference of 0 (so constructive interference occurs) Or there is a phase difference of $2\pi n$ where n is an integer	3
Total for question 13		4

Question Number	Answer	Mark
14(a)	LED, power supply and ammeter, in series (1) (allow diode for LED) (1) Method to vary the potential difference across the LED (1) LED connected in forward bias and voltmeter connected in parallel with LED (1) <u>Example circuit</u> 	3
14(b)	Current = 37 (mA) read from graph (1) (allow range 36 to 38 mA) Use of $P = VI$ (1) Power of LED = 0.0814 W (1) (allow range 0.079 to 0.084 W) <u>Example calculation</u> $P = 2.2 \text{ V} \times 37 \times 10^{-3} \text{ A} = 0.0814 \text{ W}$	3
14(c)	Between 0 V and 1.6 V the resistance of the LED was (almost) infinite (1) (As p.d. increased) above 1.6 V, the resistance of the LED decreased (1) Max 1 mark for statement that resistance is initially (almost) infinite and then decreases	2
Total for question 14		8

Question Number	Answer	Mark
15(a)	Use of cross-sectional area = width $\times$ thickness (1)	4
	Use of factor of 6 to determine total length of metal strips (1)	
	Or Use a factor of 6 to determine the resistance of one strip (1)	
	Use of $R = \frac{\rho l}{A}$ (1)	
	$\rho = 4.8 \times 10^{-7} \Omega \text{ m}$ (1)	
	<u>Example calculation</u> $A = 1.40 \times 10^{-3} \text{ m} \times 0.23 \times 10^{-3} \text{ m} = 3.22 \times 10^{-7} \text{ m}^2$ $l_{\text{total}} = 6 \times 18 \times 10^{-3} \text{ m} = 0.108 \text{ m}$ $\rho = \frac{0.16 \Omega \times 3.22 \times 10^{-7} \text{ m}^2}{0.108 \text{ m}} = 4.77 \times 10^{-7} \Omega \text{ m}$	
15(b)	The cross-sectional area of each metal strip is $\frac{\text{volume}}{l}$ (1)	3
	So the resistance of each strip is $\frac{\rho l^2}{\text{volume}}$ (1)	
	So resistance is proportional to l^2 (which gives a straight line through the origin) (1)	
Total for question 15		7

Question Number	Answer	Mark
16(a)	Direct the laser away from people's eyes Stand behind the laser Avoid directing the laser at reflective surfaces (1)	1
16(b)	The distance from the central maximum to any other maximum (1) or the distance between two maxima of the same order The (perpendicular) distance between the diffraction grating and the screen (1)	2
16(c)(i)	$\theta = 9^\circ$ (1) Calculates d (1) Use of $n\lambda = d \sin \theta$ (1) $\lambda = 630 \text{ (nm)}$ (1) <u>Example calculation</u> $\theta = \frac{18^\circ}{2} = 9^\circ$ $d = \frac{10^{-3} \text{ m}}{250} = 4 \times 10^{-6} \text{ m}$ $\lambda = 4 \times 10^{-6} \text{ m} \times \sin(9^\circ) = 626 \text{ nm}$	4
16(c)(ii)	Use of $n\lambda = d \sin \theta$ with $\theta = 90^\circ$ (1) $n_{\max} = 6$ (1) (ecf from (c)(i)) <u>Example calculation</u> $n_{\max} = \frac{4 \times 10^{-6}}{630 \times 10^{-9}} = 6.3$	2
Total for question 16		9

Question Number	Answer	Mark
17(a)	Use of $n = \frac{c}{v}$ $v = 2.26 \times 10^8 \text{ m s}^{-1}$ <u>Example calculation</u> $v = \frac{3.00 \times 10^8 \text{ m s}^{-1}}{1.33} = 2.256 \times 10^8 \text{ m s}^{-1}$	(1) (1) <

Question Number	Answer	Mark
18(a)	Oscillations / waves <u>reflect</u> from (each) end of the cable (1)	3
	The (reflected) waves interfere / superpose (1)	
	A node forms where there is destructive interference	
	Or An antinode forms where there is constructive interference (1)	
18(b)	Point X has a large / maximum amplitude (1)	3
	At point X the displacement varies (between maximum displacement and zero displacement) (1)	
	At point Y the cable always has zero displacement (1)	
	Or At point Y the cable is stationary	

18(c)(i)	Calculates mass per unit length (1) $\mu = 24.1 \text{ (kg m}^{-1}\text{)}$ (1) <u>Example calculation</u> $\mu = \frac{2.10 \times 10^3 \text{ kg}}{87.0 \text{ m}}$ $\mu = 24.14 \text{ kg m}^{-1}$	2
18(c)(ii)	Use of $W = mg$ (1) Use of $T = \frac{W}{\text{number of cables}}$ (1) Use of $v = \sqrt{\frac{T}{\mu}}$ (1) Use of $v = f\lambda$ with $\lambda = 320 \text{ m}$ or $\lambda = 7 \text{ m}$ (1) Or Use of $v = f\lambda$ with $f = 280 \text{ Hz}$ Lowest possible frequency produced by standing wave on longest cable = 1.1 Hz Or Lowest possible frequency produced by standing wave on shortest cable = 48 Hz (1) Or Length of cable needed to give lowest frequency of 280 Hz = 0.60 m Lowest frequency waves produced < 280 Hz so humming is not produced by standing waves on the suspending cables (1) Or length of cable is not within range 3.5 to 160 m so humming is not produced by standing waves on the suspending cables <u>Example calculation</u> $W = 140 \times 10^6 \text{ kg} \times 9.81 \text{ N kg}^{-1} = 1.37 \times 10^9 \text{ N}$ $T = \frac{1.37 \times 10^9 \text{ N}}{500} = 2.74 \times 10^6 \text{ N}$ $v = \sqrt{\frac{2.74 \times 10^6 \text{ N}}{24 \text{ kg m}^{-1}}} = 338 \text{ m s}^{-1}$ $f = \frac{338 \text{ m s}^{-1}}{320} = 1.06 \text{ Hz} \text{ or } f = \frac{338 \text{ m s}^{-1}}{7} = 48.3 \text{ Hz}$ Lowest frequency waves produced < 280 Hz so humming is not produced by standing waves on the suspending cables	6
	Total for question 18	14

Question Number	Answer	Mark
19(a)	A <u>photon</u> (incident on a surface) is <u>absorbed</u> by an atom / electron (1) Or A <u>photon</u> (incident on a surface) collides with an atom / electron An electron gains energy and is emitted (from the surface) (1)	2
19(b)	(To cause the photoelectric effect) the energy (of a photon) must be greater than the work function (of the photocathode) (1) Or (to cause the photoelectric effect) the frequency (of a photon) must be greater than the threshold frequency (of the photocathode) Photon energy is proportional to frequency, so photons below a certain frequency / energy cannot cause the photoelectric effect (1)	2
19(c)	Use of $1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$ (1) Use of $E = hf$ (1) Use of $v = f\lambda$ (1) Comparison of 840 nm with 700 nm and conclusion all wavelengths of visible light can be detected (1) Or Comparison of $2.85 \times 10^{-19} \text{ J}$ with $2.37 \times 10^{-19} \text{ J}$ and conclusion all wavelengths of visible light can be detected Or Comparison of 1.78 eV with 1.48 eV and conclusion all wavelengths of visible light can be detected Or Comparison of $3.57 \times 10^{14} \text{ Hz}$ with $4.29 \times 10^{14} \text{ Hz}$ <u>Example calculation</u> $E = 1.48 \text{ eV} \times 1.6 \times 10^{-19} \text{ J eV}^{-1} = 2.37 \times 10^{-19} \text{ J}$ $f_{\text{threshold}} = \frac{2.37 \times 10^{-19} \text{ J}}{6.63 \times 10^{-34} \text{ Js}} = 3.57 \times 10^{14} \text{ Hz}$ $\lambda_{\text{threshold}} = \frac{3 \times 10^8 \text{ m s}^{-1}}{3.57 \times 10^{14} \text{ Hz}} = 840 \times 10^{-9} \text{ m}$ 700 nm < 840 nm so all wavelengths of visible light can be detected	4

19(d)	Use of $E_k = \frac{1}{2}mv^2$ (1) Use of $V = \frac{W}{Q}$ (1) Final kinetic energy = 1.81×10^{-17} (J) (1) <u>Example calculation</u> Initial $E_k = 0.5 \times 9.11 \times 10^{-31} \text{ kg} \times (1.35 \times 10^6 \text{ m s}^{-1})^2 = 8.30 \times 10^{-19} \text{ J}$ $W = 108 \text{ V} \times 1.6 \times 10^{-19} \text{ C} = 1.73 \times 10^{-17} \text{ J}$ Final kinetic energy (= $1.73 \times 10^{-17} \text{ J} + 8.30 \times 10^{-19} \text{ J}$) = $1.81 \times 10^{-17} \text{ J}$	3
19(e)	EITHER Use of $V = IR$ to calculate current in circuit (1) Calculates total p.d across resistors A to D (1) Use of sum of e.m.f. = sum of p.d (1) Internal resistance = $1.20 \text{ M}\Omega$ (1) OR Calculates total p.d. across resistors A to D (1) Uses ratio of resistance = ratio of p.d. (1) Correct values substituted into ratio equation (1) Internal resistance = $1.20 \text{ M}\Omega$ (1) <u>Example calculation</u> $I = \frac{108 \text{ V}}{85 \times 10^3 \Omega} = 1.27 \times 10^{-3} \text{ A}$ $V = 1960 - 4 \times 108 = 1530 \text{ V}$ $r = \frac{1530 \text{ V}}{1.27 \times 10^{-3} \text{ A}} = 1.20 \times 10^6 \Omega$	4
Total for question 19		15

